



# DATACARD® SP25 PLUS CARD PRINTER



## INNOVATIVE APPLICATIONS

Use the Datacard® SP25 Plus card printer to produce full-color photo IDs, monochrome cards, rewritable cards or cards that utilize a combination of all 3 technologies:

- Corporate visitor ID cards
- Employee ID cards
- Student IDs with rewritable class schedules
- Patient ID cards with rewritable appointments/schedules
- Transit cards with rewritable ticketing details or schedules
- Retail cards with rewritable loyalty points
- Ski lift tickets and other recreation cards

## Affordable and flexible dual-function printing

The Datacard® SP25 Plus card printer offers both full-color/monochrome card printing and innovative rewritable card technology in a flexible, dual-function design. This unique, affordable printer is an ideal solution for low-volume applications or requirements.

- **Outstanding color and monochrome card printing.** The SP25 Plus card printer makes it easy to produce attractive cards with high-quality, full-color or single-color photos, graphics and text. Advanced Imaging Technology™ helps ensure bold, vivid color, precise bar code printing and sharp fine-line details.
- **Remarkable rewritable technology.** The SP25 Plus card printer delivers single-color photos and text on rewritable cards with excellent image quality. Rewritable cards feature a clear, heat-sensitive layer that can be erased and rewritten over 500 times. They offer an affordable way to update cards with frequently changing data or create reusable cards, such as temporary visitor IDs, because rewritable cards eliminate the supply costs of reissuance.
- **Simple operation and maintenance.** To help ensure exceptional ease of use, the SP25 Plus card printer features quick-change supplies and input hopper for batch issuance in a compact design. Everything you need to get started comes in a color supply kit, including a color ribbon, blank cards and cleaning supplies.

# DATACARD® SP25 PLUS CARD PRINTER




Error-free ribbon loading for fast switching between color/monochrome printing and rewritable printing



100 card input hopper



Output hopper holds 20 .030 in. (.76mm) cards



Optional magnetic stripe encoding and smart card personalization



USB port for industry standard connectivity

The Datacard® SP25 Plus card printer is the only system that comes standard with full-color, monochrome and rewritable card printing capabilities.

## Standard features

### Print capabilities

- One-sided printing
- Edge-to-edge continuous-tone, full-color, black-and white printing
- Edge-to-edge rewritable printing
- Alphanumeric text, logos and digitized signatures
- Variety of bar codes
- Background patterns

### Advanced Imaging Technology™

#### Print speed

- Full-color printing: 30 seconds per card
- Monochrome (black) printing: 7.2 seconds per card
- Rewritable printing: 12.4 seconds per card (full card erase and rewrite)

#### Capacity

- Automatic 100-card input hopper
- Input hopper holds 100 cards/.030 in. (.76mm) cards

#### Printer driver

- User-adjustable image and color controls
- Stand-alone driver diagnostics
- Color image and test card preview
- Online user help
- Add text, image or pattern to topcoat
- Supply usage tab

#### User-friendly operation

- Audible and visual message prompts
- Continuous cleaning roller
- Operator-replaceable printheads
- Error-free ribbon loading

#### Warranties

- 24-month standard depot warranty
- 24-month printhead warranty (no pass restrictions)

## Options

### Magnetic stripe encoding

- ISO: IAT or NTT
- Dual high- and low-coercivity
- Tracks 1, 2 and 3 (1 track for NTT)

### Smart card personalization

- Contact/contactless all-in-one reader

## Specifications

### Physical dimensions

- 16.5 in. L x 7.78 in. W x 9 in. H
- (419 mm x 198 mm x 229 mm)

### Weight

- Less than 9 lbs (4 kg) depending on printer configuration options

### Print resolution

- 300 dots per inch, 256 shades

### Electrical requirements

- 100/120V, 50/60 Hz
- 220/240V, 50/60 Hz

### Plastic cards accepted

- ISO ID-1/CR-80 size cards
- 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm)
- PVC with glossy laminate surface
- Other core materials with PVC overlaminates are optional
- Mitsubishi ThermoRewrite blue card

### Card thicknesses accepted

- 0.009 in. to 0.055 in.
- (0.2286 mm to 1.397 mm)
- 0.03 in. optimal for rewritable cards

### Operating environment

- 60°F to 95°F (15°C to 35°C)
- 20% to 80% non-condensing humidity

### Storage environment

- 5°F to 140°F (-15°C to 60°C)
- 10% to 90% humidity

### Operating system support for printer driver

- Microsoft® Windows 8 (32/64 bit)
- Windows 7 (32/64 bit)
- Windows XP (32 bit)
- Windows Server 2008 (64 bit)
- Windows Server 2003 (32 bit)
- Datacard® Open Platform printer driver for non-Windows platforms

### Agency approvals

- CE, UL, cUL, RoHS compliant: EU, CCC (contact local representative for additional regional approvals)

## Supplies

### Datacard® Certified Supplies featuring Intelligent Supplies Technology™

- Automatic ribbon identification and validation
- Automatic printer settings and offsets
- Low ribbon warning
- Ribbon saver

#### Supply kits include:

- 125 blank cards (blank or with Hi-Co magnetic stripe)
- One ribbon (125 yield) YMCKT or ymckT short panel
- One adhesive cleaning sleeve
- One cleaning card

#### Ribbon kits include:

- One roll of ribbon:
  - YMCKT
  - ymckT
  - Black HQ
- One adhesive cleaning sleeve
- One isopropanol cleaning card

#### Cards

- 125 blank white cards
- 125 blank white cards with Hi-Co magnetic stripe
- 100 rewritable cards with PVC back
- 100 rewritable cards with HiCo magnetic stripe and PVC back

#### Cleaning supplies

- Adhesive cleaning sleeve kit
- Isopropanol cleaning card kit
- Isopropanol cleaning pen

Datacard Group sales channels are your exclusive source for Datacard® Certified Supplies.

Datacard® SP Plus Series card printers require the use of Datacard Certified Supplies in order to print properly.

# Datacard Group

## CORPORATE HEADQUARTERS

11111 Bren Road West  
Minnetonka, Minnesota 55343-9015  
www.datacard.com